

PoE-Repeater, kaskadierbar

Product Images



Short Description

802.3af/802.3at/High-Power PoE an Remote-Gerät High-Power-Midspan-PoE-konform zur Vereinfachung von Bereitstellung und Installation Erweiterte PoE-Verbindung für weitere 100 Meter 2 integrierte Ausgänge für 1 PoE und 1 Non-PoE-Geräte Einfache Plug-and-Play-Installation Keine zusätzliche Stromversorgung erforderlich Mehrere PoE-Verstärker können durch Daisy-Chain zur Reichweitenverlängerung eingesetzt werden

Description

Extend the reach of your PoE-Plus devices For system integrators looking for a professional solution to help extend their PoE (802.3af/at) network, POR-0200 is the perfect accessory to increase your network performance. Normal cable runs only reach 100 meters, but with POR-0200 installers can extend the PoE network performance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining* multiple PoE repeaters. * Maximum distance depends on the required Wattage of the PD. Simple yet durable, no software required As a PoE-Plus Repeater, POR-0200 receives all power from the Power Sending Equipment (PSE), such as a PoE-Plus switch. This means that POR-0200 uses no external power supply, making it the most flexible option for system integrators looking for an easy, affordable solution to increase the distance to the attached devices on a network. POR-0200 has 3 RJ-45 ports for easy deployment, 1 "IN" port that accepts the power and data for the first 100 meters, and 2 "OUT" ports for 1 PoE (power + data) and 1 non-PoE (data only) installation, that boosts and extends the device an additional 100 meters. With a durable metal housing, POR-0200 fits into any tight deployments. Applications POR-0020 is a long-ranged solution for deploying PoE IP Camera and any Fast Ethernet PoE PD powered by 802.3at PSE.

Additional Information

802.3af PoE	1
Code des Harmonisierten Systems (HS)	851762
Zolltariflicher Warencode (TARIC)	8517620000
Farbe	Grey
EAN	4015867185575
Modellnummer	POR-0200
Dimensions (W x D x H).	130 x 90 x 28 mm
Produktgewicht (kg)	0,4
Operating humidity.	5% RH ~ 95% RH
Operating temperature.	0°C ~ 50°C
Lieferumfang	POR-0200 Quick Installation Guide
Data Rate.	100Mbps
Indikator	Power, PoE In, PoE Out
Befestigung	Wall mount
Cascadable.	Ja
Standards	IEEE 802.3 10Base-T, Ethernet IEEE 802.3u 100Base-TX, Fast Ethernet IEEE 802.3x Ethernet Flow ControlIEEE 802.3 10Base-T, Ethernet IEEE 802.3u 100Base-TX, Fast Ethernet IEEE 802.3x Ethernet Flow Control

