

SFP-4380, 1.25Gbps Single-mode BIDI(WDM) Industrial SFP Transceiver, 60km, TX 1550nm / RX 1310nm, -40°C to 85°C

Product Images



Short Description

- -20°C to 85°C operating temperature range
- Compliant with Fast Ethernet standard
- IEEE 802.3z Gigabit Ethernet compliant
- Provides simplex LC connector
- RoHS compliant and Lead Free
- Low EMI with metal housing
- 3.3V Single power supply
- Hot-swappable

Description

LevelOne Infinity Small Form Factor Pluggable (SFP) transceiver is compatible with the Small Form Factor Pluggable Multi-Sourcing Agreement (MSA). It complies with Gigabit Ethernet as specified in IEEE Std 802.3, as well as the RoHS compliant and lead-free per Directive 2002/95/EC. This Hot-swappable SFP transceiver offers the latest industry standard in full-duplex Ethernet connectivity and withstand under wide range temperature operation. Moreover, this BIDI SFP transceiver enables bidirectional communication over single fiber link.

Additional Information

Gigabit single-mode LC	1
Harmonized System (HS) code.	851762
Customs product code (TARIC).	8517620000
Fiber Optical Mode.	Single-Mode
Transceiver Type.	BIDI SFP
Grade.	Industrial
Dimensions (W x D x H).	14 x 56.6 x 8.4 mm
Product weight (kg).	0,12
Wavelength (nm).	TX 1550 / RX 1310
Package Contents.	SFP-4380
Color.	Silver
EAN.	4015867181133
Model Number.	SFP-4380

