标 记	处 数	分 区	更 改	日 期



A Direction



B Direction



Notes:

1. Plug: JT007/ST2 Clear injection no scrath and dirt;
2. Cable: H03VVH2-F 2*0.75mm² Jacket 3.5*5.7±0.2 Conductor 24*0.198±0.004 Core Ø2.2±0.1
   Cable Mark: ◁VDE▷ H03VVH2-F 2*0.75mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD
3. Test: Hi-pot: lnner Voltage AC2500V/1S External Voltage AC4000V/1S
   current leakage 1mA, insulation resistance no less than 5MΩ, no strike out;

除非另有说明，首明公差按下表：
TOLERANCE ACCORDING TO THIS FORM , UNLESS OTHERWISE INDICATED

尺寸标注 DIMENSION	公差 TOLERANCE 长度 LENGTH	角度 ANGLE
<200	±0.1	±0.5°
200~500	±0.3	
500~800	±0.5	
<800	±1.0	

第三角度投影 THE THIRD ANGLE PROJECTION			第X张	共X张	
版本 VERSION	A	比例 PROPORTION	1:1	单位 UNIT	mm	图幅 MAPS	A4
文件位置 FILE LOCATION					
图号 FIGURE NO		树脂材料 RESIN MATERIALS			
模号 DIE NO.		收缩率 SHRINKAGE			

设计 DESIGN		产品名称 PRODUCTOR NAME	112161
审核 AUDIT			
批准 APPROVAL			

equip®